

SAFETY DATA SHEET

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: FLANIGAN PEANUT BUTTER
Product Name: FLANIGAN PEANUT BUTTER
Revision Date: Apr 01, 2021
Version: 2.0
Distributor's Name: FLANIGAN BILT PUTTERS
Address: 12105 CRAMPTON DR - BURTON, OH 44021
Emergency Phone: 1-800-535-5053
Information Phone Number: (216) 466-1953
Fax:
Product/Recommended Uses: Coating for vinyl/plastics

Date Printed: 9/10/21
Supersedes Date: Apr 01, 2019

SECTION 2) HAZARDS IDENTIFICATION

Classification

Aerosols - Category 1
Gases Under Pressure - Liquefied Gas
Aspiration Hazard - Category 1
Skin Irritation - Category 2
Reproductive Toxicity - Category 2
Specific Target Organ Toxicity - Repeated Exposure - Category 2
Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) - Category 3

Pictograms



Signal Word

Danger

Hazardous Statements - Physical

H222 - Extremely flammable aerosol.
H280 - Contains gas under pressure; may explode if heated.

Hazardous Statements - Health

H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H361 - Suspected of damaging fertility or the unborn child.
H373 - May cause damage to organs through prolonged or repeated exposure.
H336 - May cause drowsiness or dizziness.

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

Precautionary Statements - Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves, protective clothing, eye protection and face protection.

P264 - Wash hands thoroughly after handling.

P260 - Do not breathe mist, vapors or spray.

P271 - Use only outdoors or in a well-ventilated area.

Precautionary Statements - Response

P314 - Get medical attention if you feel unwell.

P308 + P313 - IF exposed or concerned: Get medical attention.

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331 - Do NOT induce vomiting.

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P332 + P313 - If skin irritation occurs: Get medical attention.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a POISON CENTER or doctor if you feel unwell.

Precautionary Statements - Storage

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P403 + P405 - Store in a well-ventilated place. Store locked up.

Precautionary Statements - Disposal

P501 - Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 3) COMPOSITION, INFORMATION ON INGREDIENTS

| CAS | Chemical Name | % By Weight |
|--------------|----------------|-------------|
| 0000106-97-8 | BUTANE | 20% - 50% |
| 0064742-49-0 | VM & P NAPHTHA | 10% - 25% |
| 0000110-54-3 | HEXANE | 10% - 20% |
| 0000074-98-6 | PROPANE | 10% - 20% |
| 0008042-47-5 | MINERAL OIL | 1% - 5% |

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Move to fresh air.

Eye Contact

Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Skin Contact

Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.

Ingestion

Rinse mouth. Call a physician or poison control center immediately. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most Important Symptoms/Effects, Acute and Delayed

No data available.

Indication of Immediate Medical Attention and Special Treatment Needed

Symptoms may be delayed.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable Extinguishing Media

Do NOT use water jet as an extinguisher, as it will spread the fire.

Specific Hazards in Case of Fire

Vapors may travel considerable distance to a source of ignition and flash back.

Fire-Fighting Procedures

Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Special Protective Actions

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.

Recommended Equipment

See section 8 if the SDS for Personal Protective Equipment.

Personal Precautions

Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Environmental Precautions

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

Methods and Materials for Containment and Cleaning up

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

SECTION 7) HANDLING AND STORAGE

General

Do not puncture or incinerate (burn) cans. Do not stick pins, nails, or any other sharp objects into opening on top of can. Do not spray in eyes. Do not take internally.

Ventilation Requirements

Use in a well-ventilated place.

Storage Room Requirements

Store and use in a cool, dry, well-ventilated area. Do not store above 120°F. See product label for additional information.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Wear safety glasses with side shields. Eyewash stations and showers should be available in areas where this material is used and stored.

Skin Protection

Use solvent-resistant protective gloves for prolonged or repeated contact.

Respiratory Protection

Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use an approved air line respirator or hood. A self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

Appropriate Engineering Controls

Ventilation should be sufficient to prevent inhalation of any vapors.

| Chemical Name | OSHA TWA (mg/m3) | OSHA TWA (ppm) | OSHA STEL (mg/m3) | OSHA Carcinogen | OSHA Skin designation | OSHA Tables (Z1, Z2, Z3) | ACGIH TWA (mg/m3) | ACGIH TWA (ppm) |
|----------------|------------------|----------------|-------------------|-----------------|-----------------------|--------------------------|-------------------|-----------------|
| BUTANE | | | | | | | | |
| HEXANE | 1800 | 500 | | | | 1 | | 50 |
| MINERAL OIL | | | | | | | [(L)]; [5 (I)]; | (L) |
| PROPANE | 1800 | 1000 | | | | 1 | | |
| VM & P NAPHTHA | 2000 | 500 | | | | 1 | [(L)]; [5 (I)]; | (L) |

| Chemical Name | NIOSH STEL (ppm) | ACGIH STEL (mg/m3) | ACGIH STEL (ppm) | ACGIH Carcinogen | ACGIH TLV Basis | ACGIH Notations | NIOSH TWA (mg/m3) | NIOSH TWA (ppm) |
|----------------|------------------|--------------------|--|------------------|------------------------|-----------------|-------------------|-----------------|
| BUTANE | | | 1000 (EX) | | CNS impair | | 1900 | 800 |
| HEXANE | | | | | CNS impair; peripheral | Skin; BEI | 180 | 50 |
| MINERAL OIL | | | | [A2]; [A4]; | URT irr | [A2]; [A4]; | | |
| PROPANE | | | Simple asphyxiant (D), explosion hazard (EX) | | Asphyxia | | 1800 | 1000 |
| VM & P NAPHTHA | | | | [A2]; [A4]; | URT irr | [A2]; [A4]; | 350 | |

| Chemical Name | NIOSH STEL (mg/m3) | OSHA STEL (ppm) | NIOSH Carcinogen |
|----------------|--------------------|-----------------|------------------|
| BUTANE | | | |
| HEXANE | | | |
| MINERAL OIL | | | |
| PROPANE | | | |
| VM & P NAPHTHA | | | |

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

| | |
|-----------------------|-----------------------------|
| Density | 5.92 lb/gal |
| Density VOC | 4.02 lb/gal |
| % VOC | 68.0% |
| <hr/> | |
| Appearance | N.A. |
| Odor Threshold | N.A. |
| Odor Description | N.A. |
| pH | N.A. |
| Water Solubility | N.A. |
| Flammability | Flash point below 73°F/23°C |
| Vapor Pressure | N.A. |
| Flash Point | -104.44°C |
| Viscosity | N.A. |
| Lower Explosion Level | N.A. |
| Upper Explosion Level | N.A. |
| Vapor Density | N.A. |
| Melting Point | N.A. |
| Freezing Point | N.A. |
| Low Boiling Point | N.A. |
| High Boiling Point | N.A. |
| Decomposition Pt | N.A. |
| Auto Ignition Temp | N.A. |
| Evaporation Rate | Slower than ether |

SECTION 10) STABILITY AND REACTIVITY

Stability

The product is stable under normal storage conditions.

Conditions to Avoid

High temperatures.

Incompatible Materials

No data available.

Hazardous Reactions/Polymerization

None known.

Hazardous Decomposition Products

Hazardous decomposition products may include carbon dioxide, carbon monoxide, and other toxic fumes.

SECTION 11) TOXICOLOGICAL INFORMATION

Skin Corrosion/Irritation

Causes skin irritation

Likely Route of Exposure

Inhalation, ingestion, skin absorption.

Serious Eye Damage/Irritation

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Based on available data, the classification criteria are not met.

Reproductive Toxicity

Suspected of damaging fertility or the unborn child.

Respiratory/Skin Sensitization

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

May cause drowsiness or dizziness

Specific Target Organ Toxicity - Repeated Exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard

May be fatal if swallowed and enters airways

Acute Toxicity

Based on available data, the classification criteria are not met.

Potential Health Effects - Miscellaneous

0000110-54-3 HEXANE

LC50 (male rat): 38500 ppm (4-hour exposure); cited as 77000 ppm (271040 mg/m3) (1-hour exposure) (15)

LC50 (rat): 48000 ppm (4-hour exposure) (16)

LC50 (rat): 73680 ppm (260480 mg/m3) (4-hour exposure) (n-hexane and isomers) (1,3)

LD50 (oral, 14-day old rat): 15840 mg/kg (3)

LD50 (oral, young rat): 32340 mg/kg (3)

LD50 (oral, adult rat): 28700 mg/kg (3,16)

0000106-97-8 BUTANE

LC50 (mouse): 202000 ppm (481000 mg/m3) (4-hour exposure); cited as 680 mg/L (2-hour exposure) (9)

LC50 (rat): 276000 ppm (658000 mg/m3) (4-hour exposure); cited as 658 mg/L (4-hour exposure) (9)

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

Based on available data, the classification criteria are not met.

Persistence and Degradability

No data available.

Bioaccumulative Potential

No data available

Mobility in Soil

No data available

Other Adverse Effects

No data available.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Under RCRA, it is the responsibility of the user of the product, to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) TRANSPORT INFORMATION

| | U.S. DOT Information | IMDG Information | IATA Information |
|----------------------------------|----------------------|-------------------|---------------------|
| UN number: | UN1950 | UN1950 | UN1950 |
| Proper shipping name: | Aerosols | Aerosols | Aerosols, flammable |
| Hazard class: | 2.1 | 2.1 | 2.1 |
| Packaging group: | N.A. | N.A. | N.A. |
| Hazardous substance (RQ): | No Data Available | | |
| Marine Pollutant: | No Data Available | No Data Available | |
| Note / Special Provision: | (LTD QTY) | (LTD QTY) | (LTD QTY) |
| Toxic-Inhalation Hazard: | No Data Available | | |

SECTION 15) REGULATORY INFORMATION

| CAS | Chemical Name | % By Weight | Regulation List |
|--------------|----------------|-------------|--|
| 0000106-97-8 | BUTANE | 20% - 50% | SARA312, VOC, TSCA, ACGIH |
| 0064742-49-0 | VM & P NAPHTHA | 10% - 25% | SARA312, VOC, TSCA, ACGIH, OSHA |
| 0000110-54-3 | HEXANE | 10% - 20% | SARA313, CERCLA, HAPS, SARA312, VOC, TSCA, ACGIH, California Proposition 65 - Male Toxicity |
| 0000074-98-6 | PROPANE | 10% - 20% | SARA312, VOC, TSCA, ACGIH, OSHA |
| 0008042-47-5 | MINERAL OIL | 1% - 5% | SARA312, TSCA, ACGIH |
| 0000108-88-3 | TOLUENE | Trace | SARA313, CERCLA, HAPS, SARA312, VOC, TSCA, RCRA, ACGIH, California Proposition 65 - Developmental, OSHA |
| 0000071-43-2 | BENZENE | Trace | SARA313, CERCLA, HAPS, SARA312, VOC, TSCA, RCRA, ACGIH, California Proposition 65 - Cancer - Developmental - Male Toxicity, OSHA |
| 0000100-41-4 | ETHYLBENZENE | Trace | SARA313, CERCLA, HAPS, SARA312, VOC, TSCA, ACGIH, California Proposition 65 - Cancer, OSHA |
| 0000091-20-3 | NAPHTHALENE | Trace | SARA313, CERCLA, HAPS, SARA312, VOC, TSCA, RCRA, ACGIH, California Proposition 65 - Cancer, OSHA, |

SECTION 16) OTHER INFORMATION


Glossary

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

HMIS

| | |
|---------------------|-----|
| Health | * 2 |
| FLAMMABILITY | 4 |
| Physical Hazard | 0 |
| Personal Protection | B |

NFPA



(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.